


# Grand écran d'affichage 4K professionnel et élégant

TH-86SQ1

Équipé de fonctionnalités professionnelles avancées offrant une solution fine, légère et évolutive simplifiant toutes les installations. 86", écran 4K Ultra HD, module Intel® Smart Display (Intel® SDM), fonctionnement 24 h/24 et 7 j/7, mode portrait, 4K Digital link, cadre mince



## KEY FEATURES

- 86", 500 cd/m<sup>2</sup>, écran IPS 4K IPS à la conception fine et élégante et fonctionnement 24 h/24 et 7 j/7
- Grande qualité d'images par la prise en charge de la technologie HDR (système HLG) qui affiche les images claires et sombres de manière réaliste
- Lecteur média USB 4K : élimine le recours à des appareils externes et permet d'effectuer des mises à jour via LAN
- Grande évolutivité via la technologie Intel® SDM ultra-fine (module Intel® Smart Display), connexion DisplayPort pour la connexion en chaîne d'écrans, fonctionnalité multi-écrans (quad, PinP, PbyP) et DIGITAL LINK 4K
- Installation aisée et flexible en mode portrait ou paysage

Grand écran d'affichage 4K professionnel et élégant. Équipé de fonctionnalités professionnelles avancées offrant une solution fine, légère et évolutive simplifiant toutes les installations.

## SPECIFICATIONS

Screen size (diagonal) (inch)	86-inch (2174 mm)
Screen size (diagonal) (mm)	2174 mm
Aspect Ratio	16:9
Panel Type	IPS Panel / Edge-LED
Effective display area (W x H) (mm)	1895.0 x 1065.9 mm
Effective display area (W x H) (inch)	74.6 x 41.9 inch
Résolution	3840 x 2160
Brightness (typ.)	500 cd/m2
Contrast Ratio	1200:1 (Typ)
Response Time	8 ms (G to G)
Terminals   HDMI In	HDMI TYPE-A Connector x 2
Terminals   DisplayPort IN	DisplayPort x 1
Terminals   DisplayPort OUT	DisplayPort x 1
Terminals   DVI-D IN/AUDIO IN (L/R)	DVI-D 24-pin x 1/ Stereo Mini Jack (M3) x 2 (Shared with PC In)
Terminals   PC IN/AUDIO IN (L/R)	Mini D-sub 15-pin x 1/ Stereo Mini Jack (M3) x 2 (Shared with DVI-D In)
Terminals   USB	USB Connector (TYPE A) x 2, DC 5 V/2 A (USB 3.0 supported)
Terminals   Serial	D-sub 9-pin x 1, RS232C Compatible
Terminals   IR IN / OUT	Stereo Mini Jack (M3) x 1 / x 1
Built-in Speaker	20 W [10 W + 10 W]
Power Requirements	110-127 V AC, 50/60 Hz, 220-240 V AC, 50/60 Hz
Power Consumption	480 W
Power Off Condition	Approx. 0.3 W
Stand-by Condition	Approx. 0.5 W
Dimensions (W x H x D) (mm)	1928 x 1099 x 86 mm
Dimensions (W x H x D) (inch)	75.9" x 43.3" x 3.4"
Carton Size (W x H x D) (mm)	2224 x 1427 x 373 mm
Carton Size (W x H x D) (inch)	87.6" x 56.2" x 14.7"
Bezel width (mm)	15.2 mm (T/B/L/R)
Bezel width (inch)	0.60 inch (T/B/L/R)
Operating Time	24 h/day
Operating Environment	Temperature : 0 °C to 40 °C / Humidity: 20% to 80% (Non-condensation)
Weight (kg)	Approx. 66.0 kg
Weight (lbs.)	Approx. 145.5 lbs
Wall-hanging pitch (inch)	23.6" x 15.8" VESA Compliant
Viewing angle [(T/B)/(L/R)]	178°/178° (CR≥10)
Terminals   Audio Out	30 W [15 W + 15 W] 10% THD
Wall-hanging pitch (mm)	600 x 400 mm VESA Compliant
Terminal   DIGITAL LINK	RJ45 x 1, 100 BASE-TX, Compatible with long reach mode and PLink™
Terminal   LAN	RJ45 x 1, 10 BASE-T / 100 BASE-TX, Compatible with PLink™
Operating Environment   Humidity	0 °C to 40 °C (32 °F to 104 °F) Altitude 0~1400 m (4593 ft)/0 °C to 35 °C (32 °F to 95 °F) Altitude 1400 ~2800 m (4593 ft to 7874 ft)
Operating environment   Temperature	20% to 80% (Non-condensation)

<b>Orientation</b>	Landscape/Portrait (Angle adjustment is not possible for portrait installation.)
<b>Tilting angle</b>	0-20 degrees forward/backward with landscape/portrait setting
<b>Terminals   Slot</b>	Intel® SDM specification Corresponding size SDM-S / SDM-L, Supply power 12 V / 5.5 A, 3.3 V / 1.1 A

URL: <https://business.panasonic.fr/systemes-visuels/th-86sq1>

## CONTACT

Web: <https://business.panasonic.fr/systemes-visuels/contact-us>