

RoboSHOT® Elite NDI®

Professional PTZ Camera

ORDERING INFORMATION

RoboSHOT 30E NDI

Black

- 999-99437-000 (North America)
- 999-99437-001 (Europe/UK)
- 999-99437-009 (Australia/New Zealand)

White

- 999-99437-000W (North America)
- 999-99437-001W (Europe/UK)
- 999-99437-009W (Australia/New Zealand)



OVERVIEW

The RoboSHOT® 30E NDI® PTZ Camera is designed with NewTek NDI® (Network Device Interface) technology, which makes it easy to share high-quality video over a local Ethernet network. It's perfect for broadcast solutions where customers need a high-end NDI camera to work with their NewTek Tricaster controller and existing NDI system, and is ideal for large meeting rooms, lecture halls and houses of worship.

The RoboSHOT 30E NDI is currently the only camera that offers full native NDI; other cameras are NDI|HX, which is suited for limited bandwidth installations. NDI technology allows multiple video and audio sources to be shared across a network. This eliminates costly direct connections, expensive cable runs, and infrastructure upgrades – while turning every source into a destination instantly available anywhere on the network.

The RoboSHOT Elite series is Vaddio's next generation of professional cameras. Designed with an 1/2.5-type Exmor R CMOS sensor, RoboSHOT Elite cameras deliver striking, high-definition video image quality. Cutting-edge image signal processing (ISP) results in better light-gathering capabilities, incredible contrast and sharp 1080p/60 video, even in dim lighting conditions.

Enhanced Wide Dynamic Range

RoboSHOT Elite cameras are equipped with enhanced wide dynamic range, which can help correct for environments with uneven lighting by making darker or over-bright areas in video more visible and detailed.

Remote Management

A web-based user interface gives the user camera control with a web browser from anywhere in the world over the IP network. Perfect for remote management, network operating centers and overall IT control.

NDI is a registered trademark of NewTek Inc.

Smooth Tri-Synchronous Motion

The Elite Series of RoboSHOT PTZ cameras is equipped with Vaddio's industry-leading Tri-Synchronous Motion technology allowing all three axes of the camera to move simultaneously for ultra-smooth, natural camera motion.


Flexible Video Outputs

Video outputs include simultaneous NDI streaming and local HDMI video output.

The RoboSHOT 30E cameras are ideal for larger spaces such as large meeting rooms, lecture halls, conference centers and houses of worship.

FEATURES

- Back-illuminated 8.51 Megapixel, high definition 1/2.5 Type Exmor R CMOS Sensor delivers 1080p/60 video
- RoboSHOT 30E models feature 30x zoom including IntelliZoom™ Image Processing
- Simultaneous HDMI and NDI streaming outputs
- Full administrative control via web interface; manage remotely while monitoring the stream separately



TECHNICAL SPECIFICATIONS

Outputs/protocols	NDI® Streaming and HDMI
Aspect ratio	HDMI: 16:9 (all resolutions) NDI Streaming: 16:9 (all resolutions)
Resolutions/frame rates	FHD: 1080p/60/59.94/50/29.97/25, 1080i/60/59.94/50 HD: 720p/60/59.94/50
Streaming resolutions/frame rates	NDI® streaming up to 1080p/60
Image device	1/2.5 Type Exmor R CMOS Sensor
Pixels	8.51 million; (8.57M Total Megapixels)
Lens/Zoom	30x zoom, 20 x optical zoom + 10x IntelliZoom, f=4.4mm wide end to 88.4mm tele end, F2 to F3.8
Horizontal FOV	70.2° wide end to 4.1° tele end
Pan angle speed	±160°, 0.35°/sec to 120°/sec
Tilt angle speed	+90, -30°, 0.35°/sec to 120°/sec
Min. working distance	229mm (wide), 800mm (tele)
Min. illumination	1.6 lux; 100+ lux recommended
Electronic Shutter Speed	1/1 to 1/10000 sec.
Backlight compensation	On/off
Aperture/detail	16 steps
Focusing system	Auto Focus / Manual Focus Mode / One-push Trigger Mode
Gain	Auto / Manual (0 to 33 dB)
White balance	Auto, ATW, Indoor, Outdoor, One-push, Manual
S/N ratio	More than 50 dB
Power	PoE+
Remote management	NewTek NDI software or equipment, IR Remote, web interface, Telnet and VISCA/RS-232 command APIs
Enhanced Wide Dynamic Range	Yes
Spotlight Compensation Mode	Yes
Noise Reduction	Yes
Presets	16 + Custom Home
Invertible	Yes
Motors	Silent BLDC Direct Drive Motors
Warranty	2 years plus option for purchasing additional 3 years
Weight	4.85 lbs (2.2 kg)
Height	6.94" (17.63 cm)
Width	7.05" (17.91 cm)
Depth	6.75" (17.15 cm)
Operating/storage temperature	0°C to +40°C (32°F to 104°F)
Operating/storage humidity	20% to 80% RH, non-condensing

Specifications are subject to change without notice.

Listed part numbers include the following items:

- 1 RoboSHOT 30E NDI Camera (in black or white)
- 1 Quick-Start Guide
- 1 PoE+ Midspan Power Injector with AC cord set(s)
- 1 Thin Profile Wall Mount (in coordinating black or white) with mounting hardware and installation manual
- 1 Vaddio IR Remote Commander



THE ART OF EASY | legrandav.com

USA P 800.572.2011 E av.vaddio.support@legrand.com
EMEA P +31.495.580.840 E av.emea.sales@legrand.com
APAC P +852.2145.4099 E av.asia.sales@legrand.com

| AV

©2019 Legrand AV Inc. 190187 5/19 Vaddio is a registered trademark of Legrand AV Inc. NDI is a registered trademark of NewTek Inc. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.

COMMERCIAL BRANDS
 Chief | Da-Lite | Middle Atlantic | Projecta | Vaddio